8" Systems

High-Volume Cable Conveyors

8" (203.2mm) diameter high-volume cable conveyors can be customized to move just about anything. Examples include pet food, powders, in-shell walnuts, peanuts and puffed rice breakfast cereal. These systems are designed to handle high volume and can operate on multiple planes.

8 inch

With our 8" tube conveyor systems, you can expect:

- Gentle material handling
- Enclosed dust-free environment
- Easy maintenance

Typically used to convey:

- Pet Food Nuts
- Coffee
- Extruded Snacks
- Frozen Food

" Cable Conveyors System Capacity:


- 8" (203.2mm) tube diameter • Moves up to 2.000 Ft³
- (56.6 M³)/hr. Moves up to 80,000 pounds/hr. 36,287 Kgs per hour

(depending on bulk density of materials)



6 inch

The Clear Way to Convey




Cablevey tubular drag conveyor systems are designed to move materials in a safe, clean, and efficient manner. Our cable and tube conveyors are ideal for moving materials and product blends in a dust and contamination-free environment. Our systems are ideal for conveying delicate, fragile, and specialty bulk materials through all phases of production and processes through to packaging.

Recently, in addition to our food-grade stainless steel systems, Cablevey has released a conveyor more suitable for materials that contain natural oils. Certain natural oils like those produced by peanuts and tree nuts might affect stainless steel adversely, and therefore some materials are better conveyed through our exclusive plastic tubing.

Our Clearvey™ Systems allow materials to move through our tubing with no adverse effects. These systems are designed with the same clean, efficient and gentle handling as our stainless-steel systems. Cablevey's Clear vey™ Systems have proven to accommodate a wide range of materials beyond peanuts and tree nuts, and the clear tubing allows the user to view the material moving through the tube ensuring proper conveying. The Clearvey[™] system offers both wet and dry tube conveyor cleaning options.

Every system is custom-specified through our engineering department. This ensures all systems are optimized to client needs. Design considerations typically include how much material can be moved without breakage...and how far, how high, and how fast you need to move materials. Bottom line: our engineers and library of system components can solve most material movement needs with cable, disc, and tube conveyor systems.

Inspection Video Camera & Conveyor Monitoring System



Install a conveyor monitoring system camera to ensure proper installation and maintenance of your Cablevey conveyor. Our cameras are diagnostic tools that run through tubular drag systems to ensure that conveyors are installed correctly.

All cameras are equipped with removable micro SD cards and self-contained LED lighting units.

Enclosed Tubular Drag Cable and Disc Conveyors to Gently Convey Your Friable Materials

5.4

7.5

25

Cable Speed

Ft/Minute Meter/Minute

Compare conveyor systems below to determine which is the right conveyor system for your needs.

In comparison to other modes of conveyance, Cablevey stands out for our energy-efficiency. This chart below compares our most commonly used motor, 5HP... compared to other common means of conveying - like chain conveyors using 2.5x more energy, to the use of pneumatic conveyors often using 10x more power.





6000 Series - Maximum 1,240 Ft³/Hour (35.4 M³)

6"-150mm

	_	

4000 Series - Maximum 525 Ft³/Hour (14.87 M³) 4"-100mm



2000 Serie 2"-50mm



	Cable	e Speed	Flow Rate					
	Ft/Minute	Meter/Minute	Ft³/Hour	Lbs./Hour*	m³/Hour	Kg./Hour		
	40	12	350	14,120	10	6,400		
	60	18	530	21,180	15	9,610		
	80	24	710	28,240	20	12,810		
	100	30	880	35,300	25	16,010		
	120	37	1,060	42,360	30	19,210		
	140	43	1.240	49.420	35	22.420		

Energy Efficient

Full Load AMP

1.6

7.2

9.5

31.7

2,000

Electric Motor Operating Costs (Cablevey uses 1 to 7.5 HP Drive Units)

85.50%

91.70%

91.70%

91.70%

Based on 460V continuous run @ \$.12 per kilowatt hour

Flow Rate

m³/Hour

Lbs./Hour*

89.50%

\$419

\$2,160

\$2,928

\$4,684

\$9,758

\$19,517

20.738

25.927 31.098

36,287

	Cable	e Speed	Flow Rate				
	Ft/Minute	Meter/Minute	Ft3/Hour	Lbs./Hour*	m³/Hour	Kg./Hour	
	40	12.19	150	6,000	4.25	2,722	
	60	18.29	225	9,000	6.37	4,082	
Ì	80	24.38	300	12,000	8.50	5,442	
,	100	30.48	375	15,000	10.62	6,803	
	120	36.57	450	18,000	12.74	8,163	
	140	43	525	21,000	14.87	9,524	

ies - Maximum 75 Ft³/hour (2.12 M³)	Cable Speed		Flow Rate			
	Ft/Minute	Meter/Minute	Ft³/Hour	Lbs./Hour*	m³/Hour	
	40	12.19	30	1,200	.85	
	60	18.29	45	1,800	1.27	
	80	24 38	60	2 400	1 70	

Based on 40 Lbs per Cubic Foot (640 Kg. per Cubic Meter)

75 3,000 2.12



Cablevey Conveyors

P O Box 148, 2397 Highway 23 Oskaloosa, Iowa 52577 U.S.A. (800) 247-3344

Tel: +1 (641) 673-8451 Fax: +1 (641) 673-7419 Email: info@cablevey.com www.cablevev.com



The Gentle Way to Convey®

© Cablevey is a registered trademark of Intraco, Inc. 08/2022



Decades of Global Experience.

Worldwide Experts in Cable & Disc Conveying Solutions.


50+

Years in Business

Countries Served



Gentle Clean Reliable Conveying



Cable Conveyor Cleaning Options


Cablevey offers both wet and dry tube conveyor cleaning options. Our tube conveyors are designed for food-grade applications, eliminating places for fines to accumulate.

Cablevey Conveyors are equipped with:

- Solid Discs (no screws or bolts)
- "Jacketed" Cables (nylon casings)
- Attached Discs (to cable)
- Stainless Steel Connectors
- Removable Equipment (for easy cleaning)

Dry Cleaning

This internal tube conveyors cleaning option is available on our 4", 6" and 8" diameter systems and involves several equipment items including:



Brush Box

A line insert that mechanically brushes accumulating fines off discs.



Wiper Disc

Urethane Wiper Disc: a disc insert that wipes away accumulating fines and particles




Sponge Disc

Sponge Disc & Sanitizing Cleaner: a disposable sponge disc that is run through the system with an applied cleaning agent.

Wet Cleaning

This option is available on our 4", 6" and 8" diameter systems. It's a multi-step internal tube conveyor cleaning process that's fast and easy:




Water Rinse

After the material has passed out of the system water can be introduced to rinse the inside of the tube, disc and cable.



Foam Agen

Foam cleaning agent is introduced into the tube environment to cleanse all internal parts of the system.



for Drying

A strategically located line insert that uses compressed air to blow accumulating fines off discs.

"We offer a full line of cable and tube conveyor cleaning mechanisms"